



Euroneema® with jacket is produced for applications where heat build-up and heavy abrasion is expected. The presented data is with a polyester jacket. This is a durable jacket with excellent abrasion / heat resistance but with NON-floating properties. If floating is a must we can also provide this rope with a TIPTO® jacket. Applications, mooring, towing, salvage lifting.

# EURONEEMA® WITH POLYESTER COVER



SPECIFIC GRAVITY	• 1,06	CONSTRUCTION	• 12-strand with cover
UV-RESISTANCE	• excellent	TCLL VALUE	• 100%
ABRASION RESISTANCE	• excellent	COLOUR	• white
CHEMICAL RESISTANCE	• good	WATERABSORPTION	• 0%
ELONGATION	• see graph	ON REQUEST	• Tipto jacket
MELTING POINT	• approx. 165°C	MARKER YARN	• blue

Art.number	Circ. (inches)	Diameter (mm)	Weight (kg/100m)	MBF (kN)
092.340	5	40	104	1303
092.344	5 1/2	44	122	1544
092.348	6	48	139	1782
092.352	6 1/2	52	164	2141
092.356	7	56	195	2283
092.360	7 1/2	60	221	2635
092.364	8	64	248	2983
092.368	8 1/2	68	286	3508
092.372	9	72	319	3938

Diameter, weight and MBF (as well as other mechanical and physical properties) are determined according ISO 2307:2005

